

# Performance Data Sheet

Omnipure Filter Company  
1904 Industrial Way  
Caldwell, Idaho 83605 2084542



## ELF XL-10 Micron Carbon Block

### IMPORTANT NOTICE

Read this Performance Data Sheet and compare the capabilities of this product with your actual water treatment needs. It is recommended that, before purchasing a water filtration device, you have your water supply tested to determine your actual water treatment needs.

### Omnipure ELF XL 10M Cartridge Applications

- \_ Commercial and Residential Drinking Water Systems
- \_ Pre- and Post- R.O. Filtration
- \_ Water Coolers
- \_ Food Service



### Specifications

| Omnipure-ELF XL 10 M   |                                     |
|------------------------|-------------------------------------|
| Micron Rating          | >98% @ 10 _m                        |
| Filter Dimensions      | 3.125" O.D. x 2.875" I.D. x 17.5" L |
| Chlorine Reduction 95% | 15,000 gallons @ 2 GPM              |
| Initial _P             | <4.0 psid @ 2.0 GPM                 |
| Carbon Weight          | 1.25 lbs.                           |
| Carbon Type            | Activated Carbon                    |

### ANSI/NSF International Standards

Tested and Certified by NSF International against ANSI/NSF Standard 42 for Taste, Odor and Chlorine Reduction.

### Warnings

|                            |             |
|----------------------------|-------------|
| Operating Temperature      | 40 - 100 _F |
| Maximum Operating Pressure | 125 psig    |

- \_ All information provided is based on data believed to be reliable. It should be used for evaluation and verification but not as a warranty.
- \_ Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Activated carbon block filters are not designed to remove bacteria or viruses.
- \_ Actual performance results may vary based on the level of organic contaminants in the influent water, changes in pH and upon other conditions that may be encountered during actual use.

### General Installation/Operation/Maintenance Requirements

- \_ Flush 5 gallons through cartridge prior to use.
- \_ Replace cartridge when 15,000 gallon capacity is reached, or when flow becomes too slow.
- \_ Install in compliance with state and local laws and regulations.
- \_ Use in cold water applications only.

### Warranty Information

Omnipure Filter Company (Omnipure) warrants that the products delivered will be free from any defects in workmanship or materials. Further, the warranty provided herein applies only when used within the product's specifications and service life, from the date of installation, beyond which time or use Omnipure is absolved of any and all liability for any use of the product. In the event of defect or non-conformity, buyer shall promptly notify Omnipure in writing, supplying proof of purchase dates, installation dates, and will protect and retain the products for investigation, or Omnipure is absolved of any and all liability for any use of the product. There are no other warranties, either merchantability or fitness, either expressed or implied.